PATENT ABSTRACTS OF JAPAN

(11)Publication numb r:

10-043902

(43)Date of publication of application: 17.02.1998

(51)Int.CI.

B23B 1/00 B23B 5/00 B23Q 15/013 G05B 19/404

(21)Application number: 08-220766

(71)Applicant: SONY CORP

(22)Date of filing:

05.08.1996

(72)Inventor: IHIRA TAKUO


SUZUKI TAKASHI

(54) DRUM WORK DEVICE AND WORK METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a drum work device and a method by which roundness can be improved.

SOLUTION: A drum work device and a method are provided with a turning angle detector 24 to detect a turning angle of a main spindle 21 to integrally rotate by holding a workpiece (a fixed drum), a cutting m chanical mechanism part 30 to work a peripheral surface of the workpiece by bringing a cutting tool into contact with the peripheral surface of the workpiece and a runout detector 41 to detect a runout of a cutting peripheral side surface in the workpiece to the main spindle 21. A command to correct a peripheral runout of the primarily machined workpiece with respective turning angles, is imparted to the cutting mechanical mechanism part 30, and a work error by the peripheral runout is eliminated, and work is performed.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of

rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of xtinction of right]